

SHARP

Be Original.

BP-20C25
BP-20C20
BP-10C20

Digital Full Colour Multifunctional System

Free to fit—Goes wherever you want

Productive Operation

- 100-sheet RSPF scans documents at 37 opm*¹ (one-sided) (BP-20C25/20C20)
- Maximum 1,850-sheet paper capacity
- Multi bypass tray feeds paper up to 256 g/m² thick
- PCL 6 (standard-equipped) and PostScript® 3™ emulation (option)

Advanced Functionality

- Rotation Sort function stacks each copy at 90 degrees to the previous one for easy retrieval
- Wireless connectivity enables easy access from mobile devices and flexible MFP placement (option)
- Sharpdesk Mobile print/scan application*² enables scanned documents to be saved to a mobile device, or files on that device to be printed
- USB port conveniently located at the front of the MFP
- Print/scan command pops up on the LCD when you insert a USB drive, allowing easy printing from or scanning to the USB drive
- Full-colour network scanning with multiple scan destinations, such as desktop*³, email, FTP server, and network folder (SMB)
- High-speed Super G3 fax and PC-Fax (option) (BP-20C25/20C20)
- Inbound routing lets you forward received faxes to a PC desktop*³, FTP server, network folder, or email address without printing to paper (option) (BP-20C25/20C20)

Reliable Security Solutions

- IPsec and SSL ensure secure network communications
- User authentication covering up to 30 users prevents unauthorised MFP use by requiring access numbers
- Retained data can be erased when it's time to replace the MFP

Enhanced Usability

- Easy-to-use control panel with 4-inch 5-line LCD
- Paper size selection window pops up automatically on LCD when paper is fed into multi bypass tray
- High Stand with doors for storing paper and toner cartridges
- Control panel tilts at various angles for easy access
- ID Card Copy function with dedicated key enables easy copying of both sides of a card onto a single page
- Scanner Program Keys store frequently used scan settings and destinations for easy, one-touch recall
- LDAP support for easy browsing of email addresses
- Red and green LED lamps light up to notify users of machine/job status
- SRDM (Sharp Remote Device Manager) allows centralised control of networked MFPs
- Small footprint*⁴ (560 × 560 mm)

*1: Originals per minute; when feeding A4 (8 1/2" x 11") sheets.

*2: Availability varies by country/region.

*3: Requires Network Scanner Tool Lite.

*4: "Footprint" refers to the part directly adjacent to the floor or desk space. The numerical value is for the MFP's base unit only.



BP-20C25



BP-20C25



BP-20C20
BP-10C20



COPY



PRINT



SCAN



FAX
BP-20C25
BP-20C20

SPECIFICATIONS

General	
Type	Desktop
Engine speed	A4 (8 1/2" x 11")*1: Max. 25/20/20 ppm A3 (11" x 17"): Max. 14/12/12 ppm
Control panel display	4-inch 5-line LCD
Paper size	Max. A3W (12" x 18"), min. A6 (5 1/2" x 8 1/2")*2
Paper capacity (80 g/m ²)	Standard: 350 sheets (250-sheet tray and 100-sheet multi bypass tray) Maximum: 1,850 sheets (350 sheets & optional 3 x 500-sheet tray)
Paper weight	Tray 1: 60 g/m ² to 105 g/m ² (16 lbs bond to 28 lbs bond) Trays 2-4 (BP-CS10/DE10): 60 g/m ² to 220 g/m ² (16 lbs bond to 80 lbs cover) Multi bypass tray: 55 g/m ² to 256 g/m ² (13 lbs bond to 140 lbs index)
Warm-up time*3	29 sec.
Memory	2 GB (copy/print shared)
Power requirements	Rated local AC voltage ±10%, 50/60 Hz
Power consumption	Max. 1.44 kW (110 V to 120 V), max. 1.84 kW (220 V to 240 V)
Dimensions (W x D x H)	[BP-20C25/20C20] 560 x 560 x 653 mm (22 1/16" x 22 1/16" x 25 23/32") [BP-10C20] 560 x 560 x 560 mm (22 1/16" x 22 1/16" x 22 1/16")
Weight (approx.)	[BP-20C25/20C20] 52 kg (112.5 lbs) [BP-10C20] 47 kg (103.7 lbs)

Copier	
Original paper size	Max. A3 (11" x 17")
First copy time*4	Colour: 11.5 sec. B/W: 8.0 sec.
Continuous copy	Max. 999 copies
Resolution	Scan: 600 x 600 dpi, 600 x 400 dpi Print: 600 x 600 dpi
Gradation	Equivalent to 256 levels
Zoom range	25% to 400% (25% to 200% using RSPF) in 1% increments
Preset copy ratios	Metric: 10 ratios (5R/5E), inch: 8 ratios (4R/4E)

Scanner	
Scan method	Push scan (via control panel) Pull scan (TWAIN-compliant application)
Scan speed*5	[Colour & B/W] Max. 37 originals/min.
Resolution	Push scan: 100, 150, 200, 300, 400, 600 dpi Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi 50 dpi to 9,600 dpi via user setting*6
File formats	TIFF, PDF, JPEG*7
Scan destinations	Scan to email/desktop*/FTP server/network folder (SMB)/USB drive


Printer	
Resolution	600 x 600 dpi
Interface	USB 2.0 (host, high-speed), 10Base-T/100Base-TX/1000Base-T, wireless LAN (IEEE 802.11 b/g/n)*9
Supported OS*10	Windows Server® 2008, Windows Server® 2008 R2, Windows Server® 2012, Windows Server® 2012 R2, Windows Server® 2016, Windows Server® 2019, Windows® 7, Windows® 8.1, Windows® 10, Mac OS 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15
Network protocols	TCP/IP
Printing protocols	LPR, Raw TCP (port 9100), FTP for downloading print files, IPP, SMB, WSD
PDL	Standard: PCL 6 emulation Option: PostScript® 3™ emulation
Available fonts	80 fonts for PCL, 136 fonts for PostScript 3 emulation

Facsimile (requires optional BP-FX10)*11	
Compression method	MH/MR/MMR/JBIG
Communication protocol	Super G3/G3
Transmission time	Less than 3 seconds*12
Modem speed	33,600 bps to 2,400 bps with automatic fallback
Transmission resolution	From Standard (203.2 x 97.8 dpi) to Ultra Fine (406.4 x 391 dpi)
Recording size	A3 to A5 (11" x 17" to 5 1/2" x 8 1/2")
Memory	64 MB (built-in)
Greyscale levels	Equivalent to 256 levels

- *1: Long-edge feeding.
- *2: Only short-edge feeding can be used with A6 (5 1/2" x 8 1/2") paper.
- *3: In a standard measurement environment. May vary depending on operating conditions and environment.
- *4: Long-edge feeding of A4 (8 1/2" x 11") sheets from 1st paper tray, using document glass, MFP in fully ready condition. May vary depending on operating conditions and environment.
- *5: Scan speed will vary depending on the type of document, the scan settings, operating conditions, and environment. Based on Sharp's A4 standard chart, using document feeder, long-edge feeding, one-sided scanning, and factory default settings.
- *6: Resolution will vary depending on the size of the scanned area.
- *7: Colour/greyscale only.
- *8: Requires Network Scanner Tool Lite.
- *9: Requires optional MX-EB18. Availability of this option varies by country/region.
- *10: Requires optional MX-PK11 for Mac OS.
- *11: Not available for the BP-10C20.
- *12: Based on Sharp's standard chart with approx. 700 characters (A4 or 8 1/2" x 11" short-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression.

- Design and specifications are subject to change without prior notice.
- PCL is a registered trademark of Hewlett-Packard Company. PostScript 3 is either a registered trademark or trademark of Adobe in the US and/or other countries. Windows Server and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple Inc., registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.

SYSTEM CONFIGURATION



Note: If you install the MFP on a floor, Sharp recommends setting it up on a stand (either the BP-DS11, BP-DS10, or BP-DE10). This set-up also requires the BP-CS10 paper tray option.

Certain optional equipment may not be available in some areas.

Distributed by: